

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® LR 3038/50 K1 B CN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Raw material for: elastomer products .

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor:

Street/POB-No.:

State/postal code/city:

Telephone:

Telefax:

Information about the Safety Data Sheet:

Wacker Chemicals (China) Co., Ltd.

Bldg. 3, 1535 Hongmei Road

Caohejing Hi-Tech Park

CHN Shanghai 200233

+86 21 6100-3400

+86 21 6100-3500

Telephone

Telefax

eMail

+49 8677 83-4888

+49 8677 886-9722

WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information (German):**Emergency Information (internat.):****Plant fire brigade****National Response Center****+49 8677 83-2222****+49 621 60-43333**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Not a hazardous substance or mixture.

2.2 Label elements

No labeling according to GHS required.

2.3 Other hazards

Product can release hydrogen. Risk of hydrogen gas formation with water, alcohols, acids, metallic salts, amines and alkalis. In combination with oxygen, the released hydrogen can form oxyhydrogen.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliary

3.2.2 Hazardous ingredients

This material does not contain any ingredients above the permitted limit(s).

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible).

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

After contact with the skin:

Wipe off excess material with cloth or paper. Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Material cannot be inhaled under normal conditions.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Further toxicology information in section 11 must be observed.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing media:**

Fires can be controlled with water spray, foam or carbon dioxide. Larger fires are best fought with alcohol-resistant aqueous film forming foam (AFFF-AR).

Extinguishing media which must not be used for safety reasons:

water jet , extinguishing powder , halones .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: carbon oxides , silicon oxides , incompletely burnt hydrocarbons , toxic and very toxic fumes . With the use of water-based extinguishing agents care is required because hydrogen can be released, which accumulates after extinguishing the fire in poorly ventilated or confined areas and may refire or cause an explosion. Foam carpets may also include hydrogen or flammable vapors, which can lead to surface bursts. Remove sources of ignition during cleaning and absorbing.

5.3 Advice for firefighters**Special protective equipment for fire fighting:**

Use respiratory protection independent of recirculated air. Keep unprotected persons away.

General information:

Fires involving SiH polysiloxane materials can be difficult to extinguish under certain circumstances.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Scoop up large quantities after dusting surfaces with sand or Fuller's earth to prevent sticking. Sweep or scrape up the spilled material and place in an appropriate chemical waste container. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Do not blend contaminated material with uncontaminated material. Do not seal collecting vessel gas-tight. Observe notes under section 7.

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Ensure adequate ventilation. Open and handle container with care. Keep container closed when not in use. Keep away from incompatible substances in accordance with section 10. Where possible, inert process equipment and blanket vessels, tanks and containers with nitrogen to reduce the available oxygen level. Contact WACKER for additional publications on the safe Handling of SiH Products. Observe information in section 8.

Precautions against fire and explosion:

Product can release hydrogen. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Do not store in virgin glass containers with basic surface. Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Do not store with: basic substances (e.g. alkalis, ammonia, amines), oxidizing agents, strong acids. Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

not applicable

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Observe standard industrial hygiene practices for the handling of chemical substances. Do not eat, drink or smoke when handling.

Personal protection equipment:

Respiratory protection

No personal respiratory protective equipment normally required.

Eye protection

Recommendation: protective goggles.

Hand protection

Use of protective gloves is recommended when handling the material.

Recommended glove types: Protective gloves made of nitrile rubber

thickness of the material: > 0,1 mm

Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of butyl rubber

thickness of the material: > 0,3 mm

Breakthrough time: > 480 min

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.

8.3 Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Property:	Value:	Method:
Appearance		
Physical state / form	paste	
Colour	transparent	
Odour		
Odour	mild	
Odour limit		
Odour limit :	no data available	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not applicable	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point	> 200 °C	(-)
Evaporation rate		
Evaporation rate	no data available	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL)	not applicable	
Vapour pressure		
Vapour pressure	not applicable	
Solubility(ies)		
Water solubility / miscibility	virtually insoluble	
Vapour density		
Relative gas/vapour density	No data known.	
Relative Density		
Relative Density	approx. 1,12 (23 °C) (Water / 4 °C = 1,00)	(DIN 53479)
Density	approx. 1,12 g/cm ³ (23 °C)	(DIN 53479)
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water	No data known.	
Auto-ignition temperature		
Ignition temperature	> 400 °C	(-)
Decomposition temperature		
Thermal decomposition	> 250 °C	(-)
Viscosity		
Viscosity (dynamic)	900000 mPa.s shear rate : 23 1/S	(-)
Molecular mass		
Molecular mass	not applicable	

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

9.2 Other information

According to previous experience autoignition of SiH containing products on a catalytically active surface may occur at a much lower temperature than expected. This applies to porous or fibrous substances including those with alkaline surfaces, such as thermal insulation and cementaceous insulating materials. Explosion limits for released hydrogen: 4 - 75.6%(V). pH Value: Product displays neutral reaction.

SECTION 10: Stability and reactivity**10.1 – 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions**

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

moisture , Heat, open flames, and other sources of ignition. Contact with contaminated piping or vessels or with corroded and rusty containers can increase the rate of hydrogen formation. Observe information in section 7.

10.5 Incompatible materials

proton-active substances . Reacts with: acids , basic substances (e.g. alkalis, ammonia, amines) . alcohols , water , moisture , oxidizing agents , catalyst . Reaction causes the formation of: hydrogen .

10.6 Hazardous decomposition products

Upon contact with the substances mentioned in 10. hydrogen . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

SECTION 11: Toxicological information**11.1 Information on toxicological effects****11.1.1 Acute toxicity****Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2000 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation**Product details:**

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by analogy

11.1.4 Respiratory or skin sensitization**Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig; Bühler	Conclusion by analogy OECD 406

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

11.1.5 Germ cell mutagenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard**Assessment:**

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

SECTION 12: Ecological information

12.1 Toxicity**Assessment:**

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability**Assessment:**

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential**Assessment:**

Polymer component: No adverse effects expected.

12.4 Mobility in soil**Assessment:**

Silicone content: Insoluble in water.

12.5 Other adverse effects

none known

12.6 Additional information

Easily separable from water by filtration.

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Risk of oxyhydrogen formation upon contact with the substances mentioned in 10. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Wastes of this material should not be mixed with other wastes. Provide measures such as vented bungs to ensure pressure relief in the waste containers. Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Containers may contain hazardous quantities of hydrogen gas. Uncleaned containers should not be reused to hold another material due to the potential for reaction between residual product and incompatible materials. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

SECTION 14: Transport information

14.1 – 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation: Not regulated for transport

Railway RID:

Valuation: Not regulated for transport

Transport by sea IMDG-Code:

Valuation: Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation: Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

15.2 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea): **ECL** (Existing Chemicals List):

This product is listed in, or complies with, the substance inventory.

Japan: **ENCS** (Handbook of Existing and New Chemical Substances):

This product is listed in, or complies with, the substance inventory.

Australia: **AICS** (Australian Inventory of Chemical Substances):

This product is listed in, or complies with, the substance inventory.

People's Republic of China: **IECSC** (Inventory of Existing Chemical Substances in China):

This product is listed in, or complies with, the substance inventory.

Safety Data Sheet

Material: 60105524

ELASTOSIL® LR 3038/50 K1 B CN

Version: 1.1 (HK)

Date of print: 11.09.2017

Date of last alteration: 06.09.2017

Canada	: DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	: PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	: TSCA (Toxic Substance Control Act Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory.
Taiwan (Republic of China).....	: TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: Taiwan REACH requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	: REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

SECTION 16: Other information**16.1 Material**

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

- End of Safety Data Sheet -